

## Surge Protective Device (SPD)

## Surge Protective Device (SPD)

Model: G0074090  
120/240 VAC Single Split-Phase



### Description

Lightning strikes and utility switching can cause voltage transients and power surges in the electrical grid. These surges travel through distribution lines and into homes or businesses, damaging sensitive electronic appliances and shortening their life. Many transients go undetected, but overtime, contribute to sudden and inexplicable failures of electrical equipment. Products that are susceptible to damage include: mobile phones, computers, televisions, appliances, smart home devices, and lighting fixtures.

Generac's whole-house surge protection device (SPD) helps protect against these damaging surges and transients by blocking them from entering homes or businesses. It has thermally protected metal oxide varistors (MOVs) that help reduce risk of thermal damage. Its compact, weather-resistant design offers installation flexibility.

Generac SPDs may be installed:

- Indoors or Outdoors
- Within a Distribution Panel on the Load Side of a 20 amp Breaker

### Standard Features

- 50 k Amp Per Phase Surge Current Capacity
- 200 k Amp Short Circuit Current Rating
- Pre-wired with 24 Inches of 12-gauge Wire L1, L2, and N
- 1/2 Inch Nipple Mount
- NEMA 4X Enclosure

**120/240 VAC****Surge Protective Device (SPD)****Specifications**

Description	Rating
Surge Current Capacity Per Phase	50 kA
Nominal Discharge Current (In)	20 kA
Short Circuit Current Rating (SCCR)	200 kA
SPD Type	Rated Type 1 or Type 2
System Voltages Available	120/240 VAC Single Split-phase
Protection Modes	L-N, L-L
Maximum Continuous Operating Voltage (MCOV)	150 L-N, 300 L-L
Voltage Protection Rating (VPR)	600V L-N, 1000V L-L
Input Power Frequency	50/60 Hz
Enclosure Rating	NEMA 4X
Operating Temperature	-4 °F through 122 °F (-20 °C through 50 °C)
Operating Humidity	5% through 95%, non-condensing
Operating Altitude	Up to 6,500 ft (2,000 m)
Agency Certification and Approvals	UL1449 4th Edition Listed Device
Warranty	2 Years

**Dimensions, Weight, and Wire Range**

<b>Length (in / mm)</b>	<b>L</b>	4.29 / 109.0
<b>Width (in / mm)</b>	<b>W1</b>	4.02 / 102.1
	<b>W2*</b>	2.68 / 68.0
<b>Depth (in / mm)</b>	<b>D</b>	2.52 / 64.0
<b>Wire Range</b>	12 gauge (24 in, pre-wired)	

\* Width without feet

