



Wired Remote Control to switch ON/OFF and monitor battery charger from remote location.

Battery Charger Remote Control Model 900-RC

Design Features

- Compatible with the following series of Battery Chargers:
 - SEC-1250UL, SEC-1280UL
 - SEC-2425UL, SEC-2440UL
- Displays operational status and charging stages using colored LEDs
- Includes 10M / 33' of RJ-45 (8P8C) cable set

2 YEAR LIMITED WARRANTY

| | MODEL NO. | 900-RC |
|-------------|--|---|
| DISPLAY | GREEN LED | Marked "POWER" – Indicates ON condition |
| | GREEN LED | Marked "FLOAT" – Indicates Float Stage |
| | YELLOW LED | Marked "ABSORPTION" – Indicates Boost / Absorption Stage |
| | RED LED | Marked "BULK" – Indicates Bulk Stage |
| CONNECTIONS | INPUT CONNECTOR | RJ-45 Modular Jack (8P8C) |
| | CONNECTING CABLE SET | 8 Conductors, RJ-45 (8P8C) plugs; Straight; Length: 10M / 33' |
| GENERAL | OPERATING TEMPERATURE | 0°C – 40°C / 32°F –104°F |
| | DIMENSIONS (W x D x H), INCHES | 2.54 x 1.0 x 4.28 |
| | DIMENSIONS (W \times D \times H), MM | 64.5 x 25.4 x 108.7 |
| | WEIGHT, LB | 0.80 |
| | WEIGHT, KG | 0.36 |

NOTE: Specifications are subject to change without notice