



DC-AC Rackmount Inverter with Transfer Relay Pure Sine Wave

Model	PSR-2200-24
	24 VDC- 120 VAC
	PSR-2200-48
	48 VDC- 120 VAC

Design Features

- Built-in 30A automatic transfer switch
- On-Line and Off-Line modes
- Load Safe algorithm
- Flexible configurable parameters
- Configurable via front panel, USB, or RS-232C
- Space saving 19" rack 2U enclosure
- Ethernet webpage monitoring
- SNMP Alarm Trap generation for NOC monitoring

2 YEAR LIMITED WARRANTY



MODEL NO.	PSR-2200-24	PSR-2200-48	
AC OUTPUT IN INVERTER MODE	OUTPUT VOLTAGE	100 - 120 VAC (User selectable) ; Default: 120 VAC	
	OUTPUT FREQUENCY	45 - 65 Hz (User Selectable) ; Default: 60Hz	
	TYPE & OUTPUT WAVE FORM	High Frequency Type ; Pure Sine Wave	
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVFORM	< 2%	
	CONTINUOUS OUTPUT POWER	2200W @ 120 VAC 2000W @ 100 VAC	
	SURGE OUTPUT POWER	4000W	
	PEAK EFFICIENCY	> 90%	> 92%
	NEUTRAL ISOLATION	<ul style="list-style-type: none"> • Neutral bonded to Chassis Ground when Inverter is supplying the load • Neutral isolated from Chassis Ground when Grid is supplying the load 	
AC OUTPUT IN BYPASS MODE	OUTPUT VOLTAGE	Same as external AC input source	
	TYPE OF OUTPUT WAVEFORM	Same as external AC input source	
	THD OF OUTPUT WAVEFORM	Same as external AC input source	
	CONTINUOUS OUTPUT POWER	2200W @ 120 VAC (Protected by 20A AC input breaker) 2000W @ 100 VAC (Protected by 20A AC input breaker)	
	RATING OF TRANSFER RELAY	30A	
	TRANSFER RELAY SWITCHING TIME	< 10ms	
DC/AC INPUT	TRANSFER TYPE	Synchronized or Unsynchronized (User selectable)	
	NEUTRAL ISOLATION	Neutral and Chassis Ground are isolated through internal relay	
	NOMINAL DC INPUT VOLTAGE	24 VDC	48 VDC
	DC INPUT VOLTAGE RANGE	20 - 34 VDC	40 - 60 VDC
	DC INPUT NO LOAD CURRENT	< 0.9A	< 0.7A
AC INPUT FROM GRID/GENERATOR	Voltage: Programmed value of inverter output voltage (100 - 120 VAC) ± 10% • Default: 120 VAC ±10% Frequency: 50/60 Hz		
DISPLAY	LCD	Alphanumeric: 2 lines x 16 characters each	
	LEDS	4 LEDS: AC GRID ; INVERTER ; BYPASS ; ALARM	
LOCAL CONTROL & MONITORING	MODE AND PARAMETER SETUP	Through Menus displayed on the LCD screen	
	MONITORING OPERATING STATUS	Through LCD screen and 4 LEDS	
REMOTE CONTROL & MONITORING	PARAMETER SETUP AND MONITORING USING USB	ASCII coded command line interface through terminal emulation	
	MONITORING USING ETHERNET / SNMP	Through computer's Web Browser and Ethernet connection • E-mail notification of faults and alarms • Notification of faults and alarms through Ethernet / SNMP Trap Messaging	
	WIRED ON/OFF CONTROL THROUGH TERMINALS MARKED ENB, ENB AND GND	To switch ON: • External + 10 to 40VDC fed to ENB and GND (< 6mA) • Short ENB and GND • Battery Positive fed to ENB	To switch ON: • External + 20 to 60VDC fed to ENB and GND (< 6mA) • Short ENB and GND • Battery Positive fed to ENB
	WIRED SIGNALLING	Signaling of faults and alarms through SPDT relay contact switching (no voltage) • Relay contact rating: 240 VAC, 16A	



samlexamerica®

DC-AC Rackmount Inverter with Transfer Relay Pure Sine Wave

Model
 PSR-2200-24
 24 VDC- 120 VAC
 PSR-2200-48
 48 VDC- 120 VAC

MODEL NO.	PSR-2200-24	PSR-2200-48
COOLING	3 fans, load / temperature controlled: <ul style="list-style-type: none"> Switch ON when load is >600W or heat sink temperature is $\geq 50^{\circ}\text{C}$ 	
DC INPUT UNDER VOLTAGE (UV) ALARM	17.0 to 23.0 VDC ; Default: 21.5 VDC (Auto reset at 0.5V > the set voltage)	34.0 to 46.0 VDC ; Default: 43.0 VDC (Auto reset at 1.0V > the set voltage)
DC INPUT OVER VOLTAGE (OV) ALARM	25.0 to 35.0VDC ; Default: 33.0VDC (Auto reset at 0.5V < the set voltage)	50.0 to 62.0 VDC ; Default: 56.0 VDC (Auto reset at 1.0V < the set voltage)
FAN FAULT ALARM	Fan stops	Fan stops
DC INPUT UNDER VOLTAGE PROTECTION (UVP)	17.0 to 23.0 VDC ; Default: 20.0 VDC	34.0 to 46.0 VDC ; Default: 40.0 VDC
DC INPUT UNDER VOLTAGE PROTECTION (UVP) RECOVERY	17.5 to 23.5 VDC ; Default: 23.0 VDC	35.0 to 47.0 VDC ; Default: 46.0 VDC
DC INPUT OVER VOLTAGE PROTECTION (OVP)	25.0 to 35.0 VDC ; Default: 34.0 VDC	50.0 to 62.0 VDC ; Default: 60.0 VDC
DC INPUT OVER VOLTAGE PROTECTION (OVP) RECOVERY	24.5 to 34.5 VDC ; Default: 33.0 VDC	49.0 to 61.0 VDC ; Default: 58.0 VDC
OUTPUT OVERLOAD (OL) PROTECTION	<ul style="list-style-type: none"> Programmable from 100% to 110% Default: 110% Shut down when load is > programmed value for > 2 sec 	
SHORT CIRCUIT PROTECTION	Shut down in case of the following: <ul style="list-style-type: none"> Output voltage is < 80V RMS for 1.2 sec Output current is > 35A for 1.2 sec 	
OVER TEMPERATURE PROTECTION	Shut down when internal heat sink temperature is $>95^{\circ}\text{C}$. Auto reset at 75°C .	
DC INPUT OVER CURRENT PROTECTION	6 pieces of 25A fuses in parallel = 150A	6 pieces of 15A fuses in parallel = 90A
AC INPUT OVER CURRENT PROTECTION	Breaker, 250 VAC, 12A	
INPUT / OUTPUT CONNECTIONS	DC INPUT	Nut and bolt: <ul style="list-style-type: none"> 5/16" 18 threads per inch Spring washer: #8
	DC CHASSIS GROUND	Terminal with cylindrical hole and set screw <ul style="list-style-type: none"> Hole diameter: 5/16" Set screw: 5/16" x 24 TPI; 3/8" length; Slotted head
	AC INPUT CONNECTION	<ul style="list-style-type: none"> Male AC Power Inlet Connector IEC 60320, C20 Detachable AC Power Cord with mating Connector IEC 60320, C19 on one end and NEMA5-15P Plug on the other end (Supplied with the unit)
	AC OUTPUT CONNECTION	NEMA5-20R Duplex Outlet
SAFETY AND EMI / EMC COMPLIANCE	SAFETY	ETL listed to UL Standard 62368-1 and CSA Standard C22.2 No. 62368-1
	EMI/EMC	Certified to comply with FCC Part 15(B), Class B
ENVIRONMENT	OPERATING TEMPERATURE RANGE	-20 to 50°C
	RELATIVE HUMIDITY	Up to 90%, non condensing
	STORAGE TEMPERATURE	-30 to 70°C
DIMENSIONS	(W X D X H) MM	482 X 410 X 87.7
	(W X D X H) INCHES	19 X 16.14 X 3.5
WEIGHT	KG	10.47
	LBS	23.08

NOTES:

- All AC power ratings in the Inverter Section are specified at Power Factor = 0.95
- All specifications given above are at ambient temperature of $25^{\circ}\text{C} / 77^{\circ}\text{F}$ unless specified otherwise
- Specifications are subject to change without notice